



Servo Motori Brushless

SERVO MOTORI - PREFERRED

- Velocità, precisione, controllo per performance al top
- Application oriented: servizio su misura, dalla progettazione all'assistenza
- Serie Preferred: per tempi di consegna ai minimi termini



TECHNICAL DATA

Motor Type

B10.36J 36 Nm - 2000 rpm - 10 poles - 400V

PERFORMANCE DATA

Type	B10.36J
Stall torque (Deltat=105°C) Mo Nm	36
Rated speed n rpm	2000
Rated power P _n kW	6.3
Rated torque (Deltat=105°C) Mn Nm	30.1
Peak torque M _{pk} Nm	144
Max speed n _{max} rpm	4000
Moment of inertia J 10 ⁻³ Kgm ²	60
Peack torque acceleration a _{pk} rad/sec ²	24000
Thermal time constant T _{th} min	41
Voltage constant k _e V _s	1.41
Torque constant k _t Nm/A	2.44
Resistance phase to phase (20°C) R _w ?	0.63
Inductance phase to phase L _w mH	11

B.E.M.F. @ rated speed E_n Vrms	296
Stall current I_o Arms	14.7
Rated current I_n Arms	12.3
Peak current I_{pk} Arms	84
Power connector size	7/1
Weight kg	30

Mechanical Data

Design	Aluminium
Degree of protection	IP 65
Bearings DE	6208 2ZC3WT
Bearings NDE	6206 2ZC3WT
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	radiation and natural convection
Vibration Level	A (normal)

Electrical Data

Poles	10
Voltage	400V
Thermal protection threshold θ_{max} °C	140