



### Servo Motori Brushless

### SERVO MOTORI ATEX - ZONA 2-22

- Zona 2 e 22 ovvero categorie 3G (gas) e 3D (polveri)



## TECHNICAL DATA

Motor Type

B28.E2Q 1.25 Nm - 6000 rpm - 8 poles - 400V

## PERFORMANCE DATA

Type	B28.E2Q
Stall torque (Deltat=105°C) Mo Nm	1.25
Rated speed n rpm	6000
Rated power P <sub>n</sub> kW	729
Rated torque (Deltat=105°C) Mn Nm	1.16
Peak torque M <sub>pk</sub> Nm	5
Max speed n <sub>max</sub> rpm	6600
Moment of inertia J 10?? Kgm <sup>2</sup>	0.31
Peack torque acceleration a <sub>pk</sub> rad/sec <sup>2</sup>	161290
Thermal time constant T <sub>th</sub> min	40
Thermal protection threshold ?max °C	140
Voltage constant k <sub>e</sub> V <sub>s</sub>	0.42
Torque constant k <sub>t</sub> Nm/A	0.73
Resistance phase to phase (20°C) R <sub>w</sub> ?	10.1

Inductance phase to phase $L_w$ mH	15.3
B.E.M.F. @ rated speed $E_n$ Vrms	264
Stall current $I_o$ Arms	1.72
Rated current $I_n$ Arms	1.59
Peak current $I_{pk}$ Arms	8.2
Power connector size	7/1

## Electrical Data

Weight kg	2
Poles	8
Voltage	400V