



### Servo Motori Brushless

### SERVO MOTORI ATEX - ZONA 2-22

- Zona 2 e 22 ovvero categorie 3G (gas) e 3D (polveri)



## TECHNICAL DATA

Motor Type

B36.D6Q 0.6 Nm - 3000 rpm - 8 poles - 400V

## PERFORMANCE DATA

Type	B36.D6Q
Stall torque (Deltat=105°C) Mo Nm	0.6
Rated speed n rpm	3000
Rated power P <sub>n</sub> kW	172.8
Rated torque (Deltat=105°C) Mn Nm	0.55
Peak torque M <sub>pk</sub> Nm	2.1
Max speed n <sub>max</sub> rpm	6600
Moment of inertia J 10?? Kgm <sup>2</sup>	0.25
Peack torque acceleration a <sub>pk</sub> rad/sec <sup>2</sup>	84000
Thermal time constant T <sub>th</sub> min	30
Thermal protection threshold ?max °C	140
Voltage constant k <sub>e</sub> V <sub>s</sub>	0.84
Torque constant k <sub>t</sub> Nm/A	1.45
Resistance phase to phase (20°C) R <sub>w</sub> ?	105

Inductance phase to phase $L_w$ mH	144
B.E.M.F. @ rated speed $E_n$ Vrms	264
Stall current $I_o$ Arms	0.4
Rated current $I_n$ Arms	0.4
Peak current $I_{pk}$ Arms	1.8
Power connector size	7/1

## Electrical Data

Weight kg	2
Poles	8
Voltage	400V