



Servo Motori Brushless

SERVO MOTORI ATEX - ZONA 2-22

- Zona 2 e 22 ovvero categorie 3G (gas) e 3D (polveri)



TECHNICAL DATA

Motor Type

B63.10Q 10 Nm - 3000 rpm - 8 poles - 400V

PERFORMANCE DATA

Type	B63.10Q
Stall torque (Deltat=105°C) Mo Nm	10
Rated speed n rpm	3000
Rated power P _n kW	2.7
Rated torque (Deltat=105°C) Mn Nm	8.75
Peak torque M _{pk} Nm	30
Max speed n _{max} rpm	6600
Moment of inertia J 10?? Kgm ²	4.27
Peack torque acceleration a _{pk} rad/sec ²	70258
Thermal time constant T _{th} min	35
Thermal protection threshold ?max °C	140
Voltage constant k _e V _s	0.94
Torque constant k _t Nm/A	1.63
Resistance phase to phase (20°C) R _w ?	1.9

Inductance phase to phase L_w mH	17.4
B.E.M.F. @ rated speed E_n Vrms	296
Stall current I_o Arms	6.1
Rated current I_n Arms	5.4
Peak current I_{pk} Arms	27.5
Power connector size	7/1

Electrical Data

Weight kg	7.2
Poles	8
Voltage	400V