



Servo Motori Brushless

SERVO MOTORI ATEX - ZONA 2-22

- Zona 2 e 22 ovvero categorie 3G (gas) e 3D (polveri)



TECHNICAL DATA

Motor Type

B71.08Q 9 Nm - 2000 rpm - 8 poles - 400V

PERFORMANCE DATA

| | |
|--|---------|
| Type | B71.08Q |
| Stall torque (Deltat=105°C) Mo Nm | 9 |
| Rated speed n rpm | 2000 |
| Rated power P _n kW | 1.7 |
| Rated torque (Deltat=105°C) Mn Nm | 8.1 |
| Peak torque M _{pk} Nm | 27.6 |
| Max speed n _{max} rpm | 6600 |
| Moment of inertia J 10?? Kgm ² | 6 |
| Peack torque acceleration a _{pk} rad/sec ² | 45695 |
| Thermal time constant T _{th} min | 37 |
| Thermal protection threshold ?max °C | 140 |
| Voltage constant k _e V _s | 1.41 |
| Torque constant k _t Nm/A | 2.44 |
| Resistance phase to phase (20°C) R _w ? | 4.03 |

| | |
|--|------|
| Inductance phase to phase L_w mH | 44.4 |
| B.E.M.F. @ rated speed E_n Vrms | 296 |
| Stall current I_o Arms | 3.7 |
| Rated current I_n Arms | 3.3 |
| Peak current I_{pk} Arms | |
| Power connector size | 7/1 |

Electrical Data

| | |
|------------------|------|
| Weight kg | 9.5 |
| Poles | 8 |
| Voltage | 400V |