



Servo Motori Brushless

SERVO MOTORI ATEX - ZONA 2-22

- Zona 2 e 22 ovvero categorie 3G (gas) e 3D (polveri)



TECHNICAL DATA

Motor Type

B71.08Q 9 Nm - 3000 rpm - 8 poles - 400V

PERFORMANCE DATA

Type	B71.08Q
Stall torque (Deltat=105°C) Mo Nm	9
Rated speed n rpm	3000
Rated power P _n kW	2.4
Rated torque (Deltat=105°C) Mn Nm	7.7
Peak torque M _{pk} Nm	27.6
Max speed n _{max} rpm	6600
Moment of inertia J 10?? Kgm ²	6
Peack torque acceleration a _{pk} rad/sec ²	45695
Thermal time constant T _{th} min	37
Thermal protection threshold ?max °C	140
Voltage constant k _e V _s	0.94
Torque constant k _t Nm/A	1.63
Resistance phase to phase (20°C) R _w ?	2.16

Inductance phase to phase L_w mH	21.5
B.E.M.F. @ rated speed E_n Vrms	296
Stall current I_o Arms	5.5
Rated current I_n Arms	4.7
Peak current I_{pk} Arms	
Power connector size	7/1

Electrical Data

Weight kg	9.5
Poles	8
Voltage	400V