



Servo Motori Brushless

SERVO MOTORI ATEX - ZONA 2-22

- Zona 2 e 22 ovvero categorie 3G (gas) e 3D (polveri)



TECHNICAL DATA

Motor Type

B71.16Q 16 Nm - 4500 rpm - 8 poles - 400V

PERFORMANCE DATA

Type	B71.16Q
Stall torque (Deltat=105°C) Mo Nm	16
Rated speed n rpm	4500
Rated power P _n kW	6
Rated torque (Deltat=105°C) Mn Nm	12.7
Peak torque M _{pk} Nm	55.2
Max speed n _{max} rpm	6600
Moment of inertia J 10?? Kgm ²	10.7
Peack torque acceleration a _{pk} rad/sec ²	51589
Thermal time constant T _{th} min	43
Thermal protection threshold ?max °C	140
Voltage constant k _e V _s	0.63
Torque constant k _t Nm/A	1.09
Resistance phase to phase (20°C) R _w ?	0.34

Inductance phase to phase L_w mH	4.1
B.E.M.F. @ rated speed E_n Vrms	296
Stall current I_o Arms	14.7
Rated current I_n Arms	11.7
Peak current I_{pk} Arms	
Power connector size	7/1

Electrical Data

Weight kg	13.5
Poles	8
Voltage	400V