



Servo Motori Brushless

SERVO MOTORI ATEX - ZONA 2-22

- Zona 2 e 22 ovvero categorie 3G (gas) e 3D (polveri)



TECHNICAL DATA

Motor Type

B10.72Q 72 Nm - 1500 rpm - 8 poles - 400V

PERFORMANCE DATA

Type	B10.72Q
Stall torque (Deltat=105°C) Mo Nm	72
Rated speed n rpm	1500
Rated power P _n kW	8.1
Rated torque (Deltat=105°C) Mn Nm	51.8
Peak torque M _{pk} Nm	305
Max speed n _{max} rpm	4000
Moment of inertia J 10?? Kgm ²	80
Peack torque acceleration a _{pk} rad/sec ²	38125
Thermal time constant T _{th} min	58
Thermal protection threshold ?max °C	140
Voltage constant k _e V _s	1.88
Torque constant k _t Nm/A	3.26
Resistance phase to phase (20°C) R _w ?	0.49

Inductance phase to phase L_w mH	7.8
B.E.M.F. @ rated speed E_n Vrms	296
Stall current I_o Arms	22.1
Rated current I_n Arms	15.9
Peak current I_{pk} Arms	122
Power connector size	7/1.5

Electrical Data

Weight kg	58
Poles	8
Voltage	400V