



Servo Motori Brushless

SERVO MOTORI ATEX - ZONA 2-22

- Zona 2 e 22 ovvero categorie 3G (gas) e 3D (polveri)



TECHNICAL DATA

Motor Type

B10.56J 56 Nm - 2000 rpm - 10 poles - 400V

PERFORMANCE DATA

Type	B10.56J
Stall torque (Deltat=105°C) Mo Nm	56
Rated speed n rpm	2000
Rated power P _n kW	9.3
Rated torque (Deltat=105°C) Mn Nm	44.5
Peak torque M _{pk} Nm	230
Max speed n _{max} rpm	4000
Moment of inertia J 10?? Kgm ²	102
Peack torque acceleration a _{pk} rad/sec ²	22549
Thermal time constant T _{th} min	56
Thermal protection threshold ?max °C	140
Voltage constant k _e V _s	1.41
Torque constant k _t Nm/A	2.44
Resistance phase to phase (20°C) R _w ?	0.34

Inductance phase to phase L_w mH	6.1
B.E.M.F. @ rated speed E_n Vrms	296
Stall current I_o Arms	22.9
Rated current I_n Arms	18.2
Peak current I_{pk} Arms	137
Power connector size	7/1

Electrical Data

Weight kg	38
Poles	10
Voltage	400V