



### Servo Motori Brushless

### SERVO MOTORI ATEX - ZONA 2-22

- Zona 2 e 22 ovvero categorie 3G (gas) e 3D (polveri)



## TECHNICAL DATA

Motor Type

B13.42I 42 Nm - 2000 rpm - 6 poles - 400V

## PERFORMANCE DATA

Type	B13.42I
Stall torque (Deltat=105°C) Mo Nm	42
Rated speed n rpm	2000
Rated power P <sub>n</sub> kW	6.8
Rated torque (Deltat=105°C) Mn Nm	32.5
Peak torque M <sub>pk</sub> Nm	120
Max speed n <sub>max</sub> rpm	3600
Moment of inertia J 10?? Kgm <sup>2</sup>	65
Peack torque acceleration a <sub>pk</sub> rad/sec <sup>2</sup>	18462
Thermal time constant T <sub>th</sub> min	50
Thermal protection threshold ?max °C	140
Voltage constant k <sub>e</sub> V <sub>s</sub>	1.41
Torque constant k <sub>t</sub> Nm/A	2.44
Resistance phase to phase (20°C) R <sub>w</sub> ?	0.53

<b>Inductance phase to phase <math>L_w</math> mH</b>	12.7
<b>B.E.M.F. @ rated speed <math>E_n</math> Vrms</b>	296
<b>Stall current <math>I_o</math> Arms</b>	17.2
<b>Rated current <math>I_n</math> Arms</b>	13.3
<b>Peak current <math>I_{pk}</math> Arms</b>	
<b>Power connector size</b>	7/1

## Electrical Data

<b>Weight kg</b>	48
<b>Poles</b>	6
<b>Voltage</b>	400V