



Servo Motori Brushless

SERVO MOTORI ATEX - ZONA 2-22

- Zona 2 e 22 ovvero categorie 3G (gas) e 3D (polveri)



TECHNICAL DATA

Motor Type

B13.98I 98 Nm - 3000 rpm - 6 poles - 400V

PERFORMANCE DATA

Type	B13.98I
Stall torque (Deltat=105°C) Mo Nm	98
Rated speed n rpm	3000
Rated power P _n kW	19
Rated torque (Deltat=105°C) Mn Nm	60.5
Peak torque M _{pk} Nm	280
Max speed n _{max} rpm	3600
Moment of inertia J 10?? Kgm ²	150
Peack torque acceleration a _{pk} rad/sec ²	18667
Thermal time constant T _{th} min	80
Thermal protection threshold ?max °C	140
Voltage constant k _e V _s	0.94
Torque constant k _t Nm/A	1.63
Resistance phase to phase (20°C) R _w ?	0.08

Inductance phase to phase L_w mH	2.2
B.E.M.F. @ rated speed E_n Vrms	296
Stall current I_o Arms	60.1
Rated current I_n Arms	37.1
Peak current I_{pk} Arms	
Power connector size	7/1.5

Electrical Data

Weight kg	76
Poles	6
Voltage	400V