



Servo Motori Brushless

SERVO MOTORI ATEX - ZONA 2-22

- Zona 2 e 22 ovvero categorie 3G (gas) e 3D (polveri)



TECHNICAL DATA

Motor Type

B16.C4Q 140 Nm - 1500 rpm - 8 poles - 400V

PERFORMANCE DATA

Type	B16.C4Q
Stall torque (Deltat=105°C) Mo Nm	140
Rated speed n rpm	1500
Rated power P _n kW	17
Rated torque (Deltat=105°C) Mn Nm	110
Peak torque M _{pk} Nm	475
Max speed n _{max} rpm	3800
Moment of inertia J 10?? Kgm ²	290
Peack torque acceleration a _{pk} rad/sec ²	16379
Thermal time constant T _{th} min	63
Thermal protection threshold ?max °C	140
Voltage constant k _e V _s	1.88
Torque constant k _t Nm/A	3.26
Resistance phase to phase (20°C) R _w ?	0.158

Inductance phase to phase L_w mH	4.70
B.E.M.F. @ rated speed E_n Vrms	296
Stall current I_o Arms	43
Rated current I_n Arms	34
Peak current I_{pk} Arms	
Power connector size	7/1.5

Electrical Data

Weight kg	119
Poles	8
Voltage	400V