



### Servo Motori Brushless

### SERVO MOTORI ATEX - ZONA 2-22

- Zona 2 e 22 ovvero categorie 3G (gas) e 3D (polveri)



## TECHNICAL DATA

Motor Type

B16.B4Q 240 Nm - 2000 rpm - 8 poles - 400V

## PERFORMANCE DATA

Type	B16.B4Q
Stall torque (Deltat=105°C) Mo Nm	240
Rated speed n rpm	2000
Rated power P <sub>n</sub> kW	31
Rated torque (Deltat=105°C) Mn Nm	148
Peak torque M <sub>pk</sub> Nm	900
Max speed n <sub>max</sub> rpm	3800
Moment of inertia J 10?? Kgm <sup>2</sup>	497
Peack torque acceleration a <sub>pk</sub> rad/sec <sup>2</sup>	18109
Thermal time constant T <sub>th</sub> min	67
Thermal protection threshold ?max °C	140
Voltage constant k <sub>e</sub> V <sub>s</sub>	1.41
Torque constant k <sub>t</sub> Nm/A	2.44
Resistance phase to phase (20°C) R <sub>w</sub> ?	0.037

Inductance phase to phase $L_w$ mH	1.40
B.E.M.F. @ rated speed $E_n$ Vrms	296
Stall current $I_o$ Arms	98
Rated current $I_n$ Arms	61
Peak current $I_{pk}$ Arms	
Power connector size	3/M10

## Electrical Data

Weight kg	173
Poles	8
Voltage	400V