



Servo Motori Brushless

SERVO MOTORI ATEX - ZONA 2-22

- Zona 2 e 22 ovvero categorie 3G (gas) e 3D (polveri)



TECHNICAL DATA

Motor Type

B16.C4Q 140 Nm - 3000 rpm - 8 poles - 400V

PERFORMANCE DATA

Type	B16.C4Q
Stall torque (Deltat=105°C) Mo Nm	140
Rated speed n rpm	3000
Rated power P _n kW	14
Rated torque (Deltat=105°C) Mn Nm	45
Peak torque M _{pk} Nm	475
Max speed n _{max} rpm	3800
Moment of inertia J 10?? Kgm ²	290
Peack torque acceleration a _{pk} rad/sec ²	16379
Thermal time constant T _{th} min	63
Thermal protection threshold ?max °C	140
Voltage constant k _e V _s	0.94
Torque constant k _t Nm/A	1.63
Resistance phase to phase (20°C) R _w ?	0.035

Inductance phase to phase L_w mH	1.06
B.E.M.F. @ rated speed E_n Vrms	296
Stall current I_o Arms	86
Rated current I_n Arms	28
Peak current I_{pk} Arms	
Power connector size	3/M10

Electrical Data

Weight kg	119
Poles	8
Voltage	400V