



### Servo Motori Brushless

### SERVO MOTORI ATEX - ZONA 2-22

- Zona 2 e 22 ovvero categorie 3G (gas) e 3D (polveri)



## TECHNICAL DATA

Motor Type

B20.D2Q 0.18 Nm - 6000 rpm - 8 poles - 400V

## PERFORMANCE DATA

Type	B20.D2Q
Stall torque (Deltat=105°C) Mo Nm	0.18
Rated speed n rpm	6000
Rated power P <sub>n</sub> kW	95
Rated torque (Deltat=105°C) Mn Nm	0.15
Peak torque M <sub>pk</sub> Nm	0.6
Max speed n <sub>max</sub> rpm	6000
Moment of inertia J 10?? Kgm <sup>2</sup>	0.02
Peack torque acceleration a <sub>pk</sub> rad/sec <sup>2</sup>	315789
Thermal time constant T <sub>th</sub> min	7
Thermal protection threshold ?max °C	140
Voltage constant k <sub>e</sub> V <sub>s</sub>	0.17
Torque constant k <sub>t</sub> Nm/A	0.29
Resistance phase to phase (20°C) R <sub>w</sub> ?	29.1

<b>Inductance phase to phase <math>L_w</math> mH</b>	22.1
<b>B.E.M.F. @ rated speed <math>E_n</math> Vrms</b>	54
<b>Stall current <math>I_o</math> Arms</b>	0.62
<b>Rated current <math>I_n</math> Arms</b>	0.52
<b>Peak current <math>I_{pk}</math> Arms</b>	2.2
<b>Power connector size</b>	8/-

## Electrical Data

<b>Weight kg</b>	0.5
<b>Poles</b>	8
<b>Voltage</b>	400V