



Servo Motori Brushless

SERVO MOTORI ATEX - ZONA 2-22

- Zona 2 e 22 ovvero categorie 3G (gas) e 3D (polveri)



TECHNICAL DATA

Motor Type

B28.D7Q 0.75 Nm - 6000 rpm - 8 poles - 400V

PERFORMANCE DATA

Type	B28.D7Q
Stall torque (Deltat=105°C) Mo Nm	0.75
Rated speed n rpm	6000
Rated power P _n kW	440
Rated torque (Deltat=105°C) Mn Nm	0.70
Peak torque M _{pk} Nm	3
Max speed n _{max} rpm	6600
Moment of inertia J 10?? Kgm ²	0.19
Peack torque acceleration a _{pk} rad/sec ²	157895
Thermal time constant T _{th} min	36
Thermal protection threshold ?max °C	140
Voltage constant k _e V _s	0.42
Torque constant k _t Nm/A	0.73
Resistance phase to phase (20°C) R _w ?	24.2

Inductance phase to phase L_w mH	38.8
B.E.M.F. @ rated speed E_n Vrms	264
Stall current I_o Arms	1.03
Rated current I_n Arms	0.96
Peak current I_{pk} Arms	5.0
Power connector size	7/1

Electrical Data

Weight kg	2
Poles	8
Voltage	400V