



**Servo Motori Brushless**

**SERVO MOTORI ATEX - ZONA 2-22**

- Zona 2 e 22 ovvero categorie 3G (gas) e 3D (polveri)



**TECHNICAL DATA**

**Motor Type**

B71.29Q 29 Nm - 3000 rpm - 8 poles - 400V

**PERFORMANCE DATA**

Type	B71.29Q
Stall torque (Deltat=105°C) Mo Nm	29
Rated speed n rpm	3000
Rated power P <sub>n</sub> kW	6.4
Rated torque (Deltat=105°C) Mn Nm	20.3
Peak torque M <sub>pk</sub> Nm	110.4
Max speed n <sub>max</sub> rpm	6600
Moment of inertia J 10?? Kgm <sup>2</sup>	20.6
Peack torque acceleration a <sub>pk</sub> rad/sec <sup>2</sup>	53592
Thermal time constant T <sub>th</sub> min	51
Thermal protection threshold ?max °C	140
Voltage constant k <sub>e</sub> V <sub>s</sub>	0.94
Torque constant k <sub>t</sub> Nm/A	1.63
Resistance phase to phase (20°C) R <sub>w</sub> ?	0.34

Inductance phase to phase $L_w$ mH	4.3
B.E.M.F. @ rated speed $E_n$ Vrms	296
Stall current $I_o$ Arms	17.8
Rated current $I_n$ Arms	12.5
Peak current $I_{pk}$ Arms	
Power connector size	7/1

## Electrical Data

Weight kg	25.5
Poles	8
Voltage	400V