



Servo Motori Brushless

SERVO MOTORI ULTRA COMPACT

- Densità di coppia incrementata del 30%
- Dimensioni ridotte del 20%
- Design sofisticato, disegnato per l'estrema regolarità della coppia erogata



TECHNICAL DATA

Motor Type

B28.D7U 0.65 Nm - 4500 rpm - 10 poles - 400V

PERFORMANCE DATA

Type	B28.D7U
Stall torque (Deltat=105°C) Mo Nm	0.65
Rated speed n rpm	4500
Rated power P _n kW	299
Rated torque (Deltat=105°C) Mn Nm	0.64
Peak torque M _{pk} Nm	2.6
Max speed n _{max} rpm	9000
Moment of inertia J 10?? Kgm ²	0.11
Thermal time constant T _{th} min	11
Voltage constant k _e V _s	0.56
Torque constant k _t Nm/A	0.97
Resistance phase to phase (20°C) R _w ?	56.9
Inductance phase to phase L _w mH	79.0
B.E.M.F. @ rated speed E _n Vrms	264

Stall current I_o Arms	0.67
Rated current I_n Arms	0.65
Peak current I_{pk} Arms	3.8
Connection type/size	8/-
Weight kg	1.31

Mechanical Data

Design	Aluminium
Degree of protection	IP 65 except A side flange
Bearings DE	6000
Bearings NDE	6000
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	radiation and natural convection
Vibration Level	A (normal)

Electrical Data

Voltage	400V
Poles	10
Thermal protection threshold θ_{max} °C	na