



Servo Motori Brushless

SERVO MOTORI ULTRA COMPACT

- Densità di coppia incrementata del 30%
- Dimensioni ridotte del 20%
- Design sofisticato, disegnato per l'estrema regolarità della coppia erogata



TECHNICAL DATA

Motor Type

B63.08U 10.9 Nm - 3000 rpm - 10 poles - 400V

PERFORMANCE DATA

Type	B63.08U
Stall torque (Deltat=105°C) Mo Nm	10.9
Rated speed n rpm	3000
Rated power P _n kW	2.7
Rated torque (Deltat=105°C) Mn Nm	8.7
Peak torque M _{pk} Nm	27.6
Max speed n _{max} rpm	6600
Moment of inertia J 10?? Kgm ²	3.2
Thermal time constant T _{th} min	10
Voltage constant k _e V _s	0.94
Torque constant k _t Nm/A	1.63
Resistance phase to phase (20°C) R _w ?	2.78
Inductance phase to phase L _w mH	21.8
B.E.M.F. @ rated speed E _n Vrms	296

Stall current I_o Arms	6.7
Rated current I_n Arms	5.3
Peak current I_{pk} Arms	24.8
Connection type/size	7/1
Weight kg	7.3

Mechanical Data

Design	Aluminium
Degree of protection	IP 65
Bearings DE	6204
Bearings NDE	6204
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	radiation and natural convection
Vibration Level	A (normal)

Electrical Data

Voltage	400V
Poles	10
Thermal protection threshold θ_{max} °C	140