



Servo Motori Brushless

SERVO MOTORI ULTRA COMPACT

- Densità di coppia incrementata del 30%
- Dimensioni ridotte del 20%
- Design sofisticato, disegnato per l'estrema regolarità della coppia erogata



TECHNICAL DATA

Motor Type

B64.15U 15.5 Nm - 3000 rpm - 10 poles - 400V

PERFORMANCE DATA

Type	B64.15U
Stall torque (Deltat=105°C) Mo Nm	15.5
Rated speed n rpm	3000
Rated power P _n kW	3.7
Rated torque (Deltat=105°C) Mn Nm	11.8
Peak torque M _{pk} Nm	51
Max speed n _{max} rpm	6000
Moment of inertia J 10?? Kgm ²	7.3
Thermal time constant T _{th} min	31
Voltage constant k _e V _s	0.94
Torque constant k _t Nm/A	1.63
Resistance phase to phase (20°C) R _w ?	0.90
Inductance phase to phase L _w mH	9.6
B.E.M.F. @ rated speed E _n Vrms	296

Stall current I_o Arms	9.5
Rated current I_n Arms	7.2
Peak current I_{pk} Arms	46.0
Connection type/size	7/1
Weight kg	9.1

Mechanical Data

Design	Aluminium
Degree of protection	IP 65
Bearings DE	6205
Bearings NDE	6303
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	radiation and natural convection
Vibration Level	A (normal)

Electrical Data

Voltage	400V
Poles	10
Thermal protection threshold θ_{max} °C	140