



Servo Motori Brushless

SERVO MOTORI ULTRA COMPACT

- Densità di coppia incrementata del 30%
- Dimensioni ridotte del 20%
- Design sofisticato, disegnato per l'estrema regolarità della coppia erogata



TECHNICAL DATA

Motor Type

B71.17U 17 Nm - 2200 rpm - 10 poles - 400V

PERFORMANCE DATA

Type	B71.17U
Stall torque (Deltat=105°C) Mo Nm	17
Rated speed n rpm	2200
Rated power P _n kW	3.2
Rated torque (Deltat=105°C) Mn Nm	13.80
Peak torque M _{pk} Nm	47.3
Max speed n _{max} rpm	5000
Moment of inertia J 10?? Kgm ²	9.8
Thermal time constant T _{th} min	40
Voltage constant k _e V _s	1.28
Torque constant k _t Nm/A	2.22
Resistance phase to phase (20°C) R _w ?	1.27
Inductance phase to phase L _w mH	16.5
B.E.M.F. @ rated speed E _n Vrms	296

Stall current I_o Arms	7.7
Rated current I_n Arms	6.2
Peak current I_{pk} Arms	29.1
Connection type/size	7/1
Weight kg	9.9

Mechanical Data

Design	Aluminium
Degree of protection	IP 65
Bearings DE	6205
Bearings NDE	6203
Lubrication grease	low & high temperature grease
Regreasing device	permanent lubrication
Cooling	radiation and natural convection
Vibration Level	A (normal)

Electrical Data

Voltage	400V
Poles	10
Thermal protection threshold θ_{max} °C	140