



## Servo Motori Brushless

### SERVO MOTORI ULTRA COMPACT

- Densità di coppia incrementata del 30%
- Dimensioni ridotte del 20%
- Design sofisticato, disegnato per l'estrema regolarità della coppia erogata



## TECHNICAL DATA

Motor Type

B28.01U 0.95 Nm - 6000 rpm - 10 poles - 400V

## PERFORMANCE DATA

| Type                                              | B28.01U |
|---------------------------------------------------|---------|
| Stall torque (Deltat=105°C) Mo Nm                 | 0.95    |
| Rated speed n rpm                                 | 6000    |
| Rated power P <sub>n</sub> kW                     | 503     |
| Rated torque (Deltat=105°C) Mn Nm                 | 0.80    |
| Peak torque M <sub>pk</sub> Nm                    | 3.8     |
| Max speed n <sub>max</sub> rpm                    | 9000    |
| Moment of inertia J 10?? Kgm <sup>2</sup>         | 0.15    |
| Thermal time constant T <sub>th</sub> min         | 13      |
| Voltage constant k <sub>e</sub> V <sub>s</sub>    | 0.42    |
| Torque constant k <sub>t</sub> Nm/A               | 0.73    |
| Resistance phase to phase (20°C) R <sub>w</sub> ? | 18.6    |
| Inductance phase to phase L <sub>w</sub> mH       | 28.5    |
| B.E.M.F. @ rated speed E <sub>n</sub> Vrms        | 264     |

|                                              |      |
|----------------------------------------------|------|
| <b>Stall current <math>I_o</math> Arms</b>   | 1.31 |
| <b>Rated current <math>I_n</math> Arms</b>   | 1.10 |
| <b>Peak current <math>I_{pk}</math> Arms</b> | 6.9  |
| <b>Connection type/size</b>                  | 8/-  |
| <b>Weight kg</b>                             | 1.48 |

## Mechanical Data

|                             |                                  |
|-----------------------------|----------------------------------|
| <b>Design</b>               | Aluminium                        |
| <b>Degree of protection</b> | IP 65 except A side flange       |
| <b>Bearings DE</b>          | 6000                             |
| <b>Bearings NDE</b>         | 6000                             |
| <b>Lubrication grease</b>   | low & high temperature grease    |
| <b>Regreasing device</b>    | permanent lubrication            |
| <b>Cooling</b>              | radiation and natural convection |
| <b>Vibration Level</b>      | A (normal)                       |

## Electrical Data

|                                                                  |      |
|------------------------------------------------------------------|------|
| <b>Voltage</b>                                                   | 400V |
| <b>Poles</b>                                                     | 10   |
| <b>Thermal protection threshold <math>\theta_{max}</math> °C</b> | na   |